



Series	R-Series LFP	Warranty	See Warranty Terms
Volts	48	BCI	GC2
Terminal Type		M8	
Included Hardware		M8 stainless bolts & washers	

### Charge

Charge Voltage Range	56.0 - 58.4V
Recommended End of Discharge Voltage	48.0 V
End of Discharge Protection Voltage	40.0 V
Recommended Charge Voltage	57.6 V

### Recommended Charge Current

0~10°C (32~50°F)	0.2C	7A
10~35°C (50~95°F)	0.5C	17A
35~50°C (95~122°F)	0.2C	7A

### Charge Mode:

- Charge at recommend voltage & current by temperature until charge current drops to  $\leq 0.05C$  (CC,CV)
- DO NOT USE TEMPERATURE COMPENSATION
- No BTS (Battery Temperature Sensor)

Max Continuous Charge Current	17 A
Max Continuous Discharge Current	35 A
Surge Current Limit	200 A (300ms)
Charge Temperature Range	0°C~55°C (32~131°F)
Discharge Temperature Range	-20°~60°C (-4~140°F)
Storage Temperature Range	-5°~45°C (23~113°F)

### Capacity

Nominal Capacity	35 AH
Total Energy	1.79 kWh
Nominal Voltage	51.2 V

### Safety

- Cylindrical LiFePO4 cells (UL1642)
- IEC62133 (cell), IEC62619(cell), UN38.3 (cell/pack)
- ROHS (cell), CE system certification, IP65 Rating

### Design

- Standard-size (BCI) ABS container for easy VRLA replacement
- Fast charge/discharge performance
- Maintenance-free operation
- Bluetooth Connectivity & dedicated IOS & Android App

### Battery Management System (BMS)

- Integrated hardware BMS inside
- Independent charge & discharge protection
- Short-Circuit Protection, Over-Voltage Protection, Low-Voltage Protection, Over-Curent Protection, Low-Temperature Protection, Over-Temperature Protection

### 48V LFP Profile


### Specifications

 SAI GLOBAL ISO 9001 Quality	Weight	15 kg	33 lbs
	Length	26.0 cm	10.24"
	Width	18.0 cm	7.09"
	Height Inc. Term.	27.3 cm	10.63"

Product measurements & weights are calculated based on sample data. Individual specifications are subject to vary due to the manufacturing process & battery components.

Container	ABS
Cover	ABS
Handles	Nylon Strap
Internal BMS Model	16S60A
Expected Cycle Life	>6000 @ 80% DOD, >3000 @ 100% DOD
Series Connection	1 UNIT MAX
Parallel Connection	6 UNITS MAX

### Detailed Illustration



ISO9001



ISO14001



OHSAS18001

