



|                   |                              |          |                    |
|-------------------|------------------------------|----------|--------------------|
| Series            | S-Series LFP                 | Warranty | See Warranty Terms |
| Volts             | 12                           | BCI      | 8D                 |
| Terminal Type     | M8                           |          |                    |
| Included Hardware | M8 stainless bolts & washers |          |                    |

### Charge

|                                      |              |
|--------------------------------------|--------------|
| Charge Voltage Range                 | 14.0 - 14.6V |
| Recommended End of Discharge Voltage | 12.0 V       |
| End of Discharge Protection Voltage  | 10.0 V       |
| Recommended Charge Voltage           | 14.4 V       |

### Recommended Charge Current

|                    |      |      |
|--------------------|------|------|
| -20~0°C (-4-50°F)  | 0.1C | 30A  |
| 0~10°C (32-50°F)   | 0.2C | 60A  |
| 10~35°C (50-95°F)  | 0.5C | 150A |
| 35~50°C (95-122°F) | 0.2C | 60A  |

### Charge Mode:

- Charge at recommend voltage & current by temperature until charge current drops to  $\leq 0.05C$  (CC,CV)
- DO NOT USE TEMPERATURE COMPENSATION
- No BTS (Battery Temperature Sensor)

|                                  |                       |
|----------------------------------|-----------------------|
| Max Continuous Charge Current    | 200 A                 |
| Max Continuous Discharge Current | 200 A                 |
| Surge Current Limit              | 1100 A (300ms)        |
| Charge Temperature Range         | -20°C~55°C (-4~131°F) |
| Discharge Temperature Range      | -20°~60°C (-4~140°F)  |
| Storage Temperature Range        | -5°~45°C (23~113°F)   |

### Capacity

|                  |          |
|------------------|----------|
| Nominal Capacity | 300 AH   |
| Total Energy     | 3.84 kWh |
| Nominal Voltage  | 12.8 V   |

### Safety

- Cylindrical LiFePO4 cells [ITR26-70/46E 4.6Ah, 26700] (UL1642)
- IEC62133 (cell), IEC62619(cell), UN38.3 (cell/pack)
- ROHS (cell), CE system certification, IP65 Rating

### Design

- Standard-size (BCI) ABS container for easy VRLA replacement
- Fast charge/discharge performance
- Display & integrated controls
- Visual state-of-charge (SOC)
- External fuse access
- Internal heating for -20°C(-4°F)~0°C(32°F) charging
- Bluetooth Connectivity & dedicated IOS & Android App
- Maintenance-free operation

### Battery Management System (BMS)

- Integrated hardware BMS inside
- Independent charge & discharge protection
- Balance Protection
- Short-Circuit Protection, Over-Voltage Protection, Low-Voltage Protection, Over-Current Protection, Low-Temperature Protection, Over-Temperature Protection

### 12V LFP Profile

### Specifications

|  |                   |         |        |
|--|-------------------|---------|--------|
|  | Weight            | 34 kg   | 75 lbs |
|  | Length            | 52.2 cm | 20.55" |
|  | Width             | 26.8 cm | 10.55" |
|  | Height Inc. Term. | 23.2 cm | 9.13"  |

Product measurements & weights are calculated based on sample data. Individual specifications are subject to vary due to the manufacturing process & battery components.

|                     |  |
|---------------------|--|
| Container           | ABS  |
| Cover               | ABS  |
| Handles             | Rope / Plastic Handle  |
| Internal BMS Model  | 4S200ATX-V2  |
| Expected Cycle Life | >6000 @ 80% DOD, >3000 @ 100% DOD                                |
| Series Connection   | 4 UNITS MAX (48V)  |
| Parallel Connection | 4 UNITS MAX (48V) or 6 UNITS MAX (12V)                           |
| Connectivity        | Up to 4S4P (in 48V configuration) or 1S6P (in 12V configuration) |

### Detailed Illustration

