



| | | | |
|-------------------|------------------------|----------|--------------------|
| Series | GEL | Warranty | See Warranty Terms |
| Volts | 2 | BCI | 2V OPzV |
| Cells | 1 | | |
| Terminal Type | F10 | | |
| Included Hardware | Threaded Insert & Bolt | | |

Charge

| | |
|----------------------------|---------------------------------------|
| Recommended Charge Current | 250 A |
| Maximum Charge Current | 750 A |
| Self-Discharge Rate | Less than 2% per month at 25°C (77°F) |
| Internal Resistance | 0.13 mΩ |

Capacity

| Capacity Affect by Temperature | 40°C (104°F) | 25°C (77°F) | 0°C (32°F) | -15°C (5°F) |
|--------------------------------|-----------------|----------------|---------------|----------------|
| | 105% | 100% | 89% | 79% |

| Hour Rate | Capacity / AMP Hour | Current / AMPs |
|-----------------|---------------------|----------------|
| @ 100 Hour Rate | 3655 AH | 36.55 A |
| @ 20 Hour Rate | 3044 AH | 152.2 A |
| @ 10 Hour Rate | 2700 AH | 270 A |

Specifications




| | | |
|-------------------|---------|---------|
| Weight | 195 kg | 430 lbs |
| Length | 48.7 cm | 19.17" |
| Width | 21.2 cm | 8.35" |
| Height Inc. Term. | 79.9 cm | 31.46" |

Product measurements & weights are calculated based on sample data. Individual specifications are subject to vary due to the manufacturing process & battery components.

| | |
|-----------|------|
| Container | ABS |
| Cover | ABS |
| Handles | None |

Cycle Life vs. Depth of Discharge



Capacity vs. Temperature

